



COMFORT 257.2 OPERATORS FOR UNDERGROUND & COLLECTIVE PARKING



RELIABLE

**Operators For
 Underground &
 Collective Parking**

FEATURES	
<ul style="list-style-type: none"> Motor unit pre-cabled Separate control unit Control vario, pre-cabled Marantec EOS programming via LED Universal mounting kit for up-and-over doors and sectional doors Anti-blocking device Soft start/soft stop/soft run Used in conjunction with Marantec opener rails. 	
SPECIFICATIONS	
SUPPLY VOLTAGE	230V AC
CURRENT INPUT	0.26KW
CONTROL VOLTAGE	24V DC, MAX 50mA
CONSUMPTION	0.7A
DRIVE	1.000N
SPEED	140mm/s
DUTY CYCLE	S2-5min 50 cars (100 operations / day)
LIFT CAPACITY	<ul style="list-style-type: none"> - For up-and-over doors up to a door width of 6,000mm and a door weight of 200kg - For single-walled sectional doors up to a door width of 6,000mm and a door weight of 200kg - For double-walled sectional doors up to a door width of 6,000mm and a door weight of 200kg
TEMPERATURE RANGE	-20° C to +60° C
PROTECTION	Motor unit IP20 Control unit IP54
DIMENSIONS	<ul style="list-style-type: none"> - Motor Unit 220x125x395mm - Control Unit small) 240x150x80mm - Control unit large 240x300x80mm
WEIGHT	<ul style="list-style-type: none"> - Total with control unit (small) 8.6kg - Total with control unit (large) 9.1kg
LIGHT	Illuminant (energy saving bulb) 11 W/E14

(The Company reserves the right to amend product specifications and information without notice.)

PLEASE CONTACT OUR SALES TEAM +(27) 31 700 8260 for further information.

PART OF THE MARANTEC COMPANY GROUP
OPENING DOORS IN SOUTH AFRICA
 PROUD SUPPORTERS AND SUPPLIERS OF:

