

# DTWC DIRECT DRIVE 230V Automation for Sprung Roller Shutters



**Cost Effective  
 DIRECT DRIVE  
 Quality Automation  
 For Spring Balanced  
 Roller Shutters**

## FEATURES

- Integrated Mechanical Limit Switches
- Thermal Overload Protection
- Crank Manual Override (crank or chain)
- Robust, Strong & Durable
- Flexible Control Options
- Up to 13 Revolutions
- Noise level <70 dB
- 1 Phase 230V

## SPECIFICATIONS

VOLTAGE	230V AC @ 50 Hz (Single Phase)
CURRENT RATING	6.5 A
TORQUE	140 Nm
MOTOR OUTPUT	0.45 kW
SPEED	12 Rpm
DUTY CYCLE	25% < operations / Hr (Dependent on door size)
SHAFT DIAMETER	30 mm (8mm keyway)
PROTECTION	IP54
OPERATOR DIMENSIONS	361 x 105 x 245 mm
WEIGHT	approx. 16 Kg

(The Company reserves the right to amend product specifications and information without notice.)

**PLEASE CONTACT OUR SALES TEAM for further information.**

**PART OF THE MARANTEC COMPANY GROUP - OPENING DOORS IN SOUTHERN AFRICA**

PROUD SUPPORTERS AND SUPPLIERS OF:

