

# MDF30-27-12HD

## Direct Drive 380V Automation for Sprung Roller Shutters



***DIRECT DRIVE***  
***Quality High Use Automation***  
***For Spring Balanced***  
***Roller Shutters***

### FEATURES

- High Use (HD)
- Integrated Limit Switches
- Crank or Chain Manual Override Options
- Integrated Safety Catch
- Robust, Strong & Durable
- Wide Range of Control Options
- 3 Phase 380V
- Thermal Overload Protection
- Higher Torque Models available up to 2000 Nm

### SPECIFICATIONS

VOLTAGE	380V AC @ 50 Hz (Three Phase)
CURRENT INPUT	2.1 A
TORQUE	270 Nm
MOTOR OUTPUT	0.75 kW
SPEED	12 Rpm
DUTY CYCLE	30 operations / Hour (Dependent on door size)
SHAFT DIAMETER	40 mm (8mm keyway)
PROTECTION	IP54
DIMENSIONS	553 x 174 x 372mm
WEIGHT	30 Kg

(The Company reserves the right to amend product specifications and information without notice.)

**PLEASE CONTACT OUR SALES TEAM for further information.**

**PART OF THE MARANTEC COMPANY GROUP - OPENING DOORS IN SOUTHERN AFRICA**

PROUD SUPPORTERS AND SUPPLIERS OF:

