

# MDF50-75-10

## Direct Drive 380V Automation for Sprung Roller Shutters



***DIRECT DRIVE***  
***Quality High Use Automation***  
***For Spring Balanced***  
***Roller Shutters***

### FEATURES

- Integrated Limit Switches
- Crank or Chain Manual Override Options
- Integrated Safety Catch
- Robust, Strong & Durable
- Wide Range of Control Options
- 3 Phase 380V
- Thermal Overload Protection
- Higher Torque Models available up to 2000 Nm

### SPECIFICATIONS

VOLTAGE	380V AC @ 50 Hz (Three Phase)
CURRENT INPUT	3.9 A
TORQUE	750 Nm
MOTOR OUTPUT	1.4 kW
SPEED	10 Rpm
DUTY CYCLE	20 operations / Hour (Dependent on door size)
SHAFT DIAMETER	50 mm (14mm keyway)
PROTECTION	IP54
DIMENSIONS	576 x 124 x 341mm
WEIGHT	41 Kg

(The Company reserves the right to amend product specifications and information without notice.)

**PLEASE CONTACT OUR SALES TEAM +(27) 31 700 8260 for further information.**

**PART OF THE MARANTEC COMPANY GROUP**  
**OPENING DOORS IN SOUTH AFRICA**

PROUD SUPPORTERS AND SUPPLIERS OF

