

MDF60-100-9

Direct Drive 380V Automation for Sprung Roller Shutters



DIRECT DRIVE
*Quality High Use Automation
 For Spring Balanced
 Roller Shutters*

FEATURES

- Integrated Limit Switches
- Crank or Chain Manual Override Options
- Integrated Safety Catch
- Robust, Strong & Durable
- Wide Range of Control Options
- 3 Phase 380V
- Thermal Overload Protection
- Higher Torque Models available up to 2000 Nm

SPECIFICATIONS

VOLTAGE	380V AC @ 50 Hz (Three Phase)
CURRENT INPUT	6.9 A
TORQUE	1000 Nm
MOTOR OUTPUT	1.5 kW
SPEED	9 Rpm
DUTY CYCLE	20 operations / Hour (Dependent on door size)
SHAFT DIAMETER	50 mm (14mm keyway)
PROTECTION	IP54
DIMENSIONS	694 x 140 x 405mm
WEIGHT	72 Kg

(The Company reserves the right to amend product specifications and information without notice.)

PLEASE CONTACT OUR SALES TEAM +(27) 31 700 8260 for further information.

PART OF THE MARANTEC COMPANY GROUP
OPENING DOORS IN SOUTH AFRICA

PROUD SUPPORTERS AND SUPPLIERS OF

