

STA1-10-24 380V/3PH 60% Spring Balanced Sectional Door Operator



**For Spring Balanced
 Sectional Doors**

FEATURES

- 3 Phase 380V
- Emergency hand chain available
- Emergency hand chain with maintenance release available (optional)
- High Use (HD)
- Integrated Limit Switches
- Integrated Safety Catch
- Robust, Strong & Durable
- Wide Range of Control Options
- Thermal Overload Protection
- Higher Torque Models available ie: 2000

SPECIFICATIONS

VOLTAGE	380V / 3 PH
CURRENT INPUT	2.0 A – 3.5A
TORQUE	100 Nm
MOTOR OUTPUT	0.37 KW
SPEED	24 Rpm
DUTY CYCLE	20 operations / Hour (Dependent on door size)
SHAFT DIAMETER	25.4mm (8mm keyway)
TEMPERATURE RANGE	-20° to +60°
PROTECTION	IP65
DIMENSIONS	409 x 104 x 245mm
WEIGHT	15 Kg

(The Company reserves the right to amend product specifications and information without notice.)

PLEASE CONTACT OUR SALES TEAM +(27) 31 700 8260 for further information.

**PART OF THE MARANTEC COMPANY GROUP
 OPENING DOORS IN SOUTH AFRICA**

PROUD SUPPORTERS AND SUPPLIERS OF:

