

STA1-12-19 380V/3PH 80% Spring Balanced Sectional Door Operator



**For Spring Balanced
 Sectional Doors**

FEATURES

- 3 Phase 380V
- Emergency hand chain available (standard)
- Emergency hand chain with maintenance release available (by request)
- High Use (HD)
- Integrated Limit Switches
- Robust, Strong & Durable
- Wide Range of Control Options
- Thermal Overload Protection

SPECIFICATIONS

VOLTAGE	380V / 3 PH
CURRENT INPUT	1.7A - 3A
TORQUE	120 Nm
MOTOR OUTPUT	0.55 kW
SPEED	19 Rpm
DUTY CYCLE	30 operations / Hour (Dependent on door size)
SHAFT DIAMETER	25.4mm (6.35mm keyway)
TEMPERATURE RANGE	-20° to +60°
PROTECTION	IP65
DIMENSIONS	438 x 191 x 245mm
WEIGHT	23 Kg

(The Company reserves the right to amend product specifications and information without notice.)

PLEASE CONTACT OUR SALES TEAM +(27) 31 700 8260 for further information.

**PART OF THE MARANTEC COMPANY GROUP
 OPENING DOORS IN SOUTH AFRICA**

PROUD SUPPORTERS AND SUPPLIERS OF:

